

STAND-ALONE DC AND 3-PHASE POWER SUPPLIES



Transportable variable supplies unit (2000W or 4000W)

Supply from mains: 3-phase 380V/400V + neutral + earth

Outputs: 2 variable DC supplies 0-250V and 1 variable AC 3-phase supply 0-430V

PROTECTION OF THE USER IN DC

- DC supplies are isolated from mains by an insulation transformer.
- The outputs are protected against surges and short-circuits.

OTHER SPECIFICATIONS

- The DC power supply is delivered from a Graetz bridge (Ripple 4%)
- The DC auxiliary outputs is with a double alternation rectification of which the ripple rate changes with the load
- Emergency stop push button - key reset
- Voltage regulation by two autotransformers
- Power cable with industrial 3-phase plug supplied
- Hard-wearing LED lamps
- Outputs on safety terminals \varnothing 4mm.
- Dimensions 710 x 600 x 375mm - Weight COMPAK20 : 82kg - Poids COMPAK40 : 89kg.

REF	COMPAK20	COMPAK40
OUTPUT 0-250VDC	8A + voltmeter & ammeter	16A + voltmeter & ammeter
OUTPUT 0-430V 3-PHASE	5A + voltmeter & ammeter	6A + voltmeter & ammeter
AUXILIARY OUTPUT 0-250V	2.5A + voltmeter & ammeter	2.5A + voltmeter & ammeter