



PeakTech
Prüf- und Messtechnik GmbH
 Gerstenstieg 4
 DE 22926 Ahrensburg

Phone: 0049 4102 42343/44
 Fax: 0049 4102 43416

[Products](#) [Waveform Generators](#) [1 CH & 2 CH Arbitrary Waveform Generators](#) [PeakTech® 4120](#)

PeakTech® 4120 PROD-ID: P 4120

[BACK](#)

1CH Arbitrary Waveform Generator, 1 μ Hz - 5 MHz

This newly designed arbitrary waveform generator with advanced graphical user control has excellent technical properties and a high variety of functions. Of particular note here are the easily control via the various menu functions, a wide range of integrated waveforms and the excellent price/performance ratio. In this way this generator is perfect for almost all tasks in education, research and development.

- **Availability: Winter 2017**
- Large 4" high resolution color TFT-Display
- New developed graphical user interface (GUI) with many functions
- 1uHz frequency resolution for whole bandwidth
- High sampling rate of 125 MS/s
- 14-Bit vertical resolution
- Integrated waveform editor (2 to 8.000 Points)
- 6 standard waveforms (Sinus, Square, Triangle, DC etc.)
- 45 arbitrary waveforms (Hamming, Gaussian, Trapezia, Tan etc.)
- SCPI and LabView support
- Software program for remote control and waveform edit
- Safety: EN 61010
- Accessories: Power cable, USB interface cable, Software for Windows, BNC-cable, Manual and SCPI protocol on CD



PICTURES

[P4120_Front.jpg \(259.0 kB\)](#)

[P4120_L.jpg \(234.8 kB\)](#)

[P4120_Rear.jpg \(215.4 kB\)](#)

SOFTWARE

[PeakTech_4125-4165_ultrawave_2.1.7.rar \(40,822.5 kB\)](#)

[PeakTech_LibUSB_Driver_Win7_8_10.rar \(4,587.2 kB\)](#)

Display	10 cm (4") TFT, 480 x 320 pixel, 65536 color, 16Bit
Frequency range Sine	1 µHz - 5 MHz
Frequency range Square	1 µHz - 5 MHz
Frequency range Pulse	1 µHz - 5 MHz
Frequency range Ramp	1 µHz - 1 MHz
Frequency range Arb.	1 µHz - 5 MHz
Frequency range Noise	5 MHz (-3dB)
Frequency resolution	1 µHz full bandwidth
Vertical resolution	14-Bit
Sampling rate	125 MS/s
Waveform length	2 pts. ... 8.000 pts
Amplitude range (50Ω)	1 mVpp ... 12.5 Vpp
Amplitude range (High Z)	1 mVpp ... 25 Vpp
Internal Memory	64 MByte
PC Interface	USB Device
Operation voltage	100 - 240 V AC; 50 / 60 Hz
Dimensions (WxHxD)	235 x 110 x 295 mm
Weight	3 kg
EAN-13	4250569404252

